

## Product Information Sheet

## C501 - LCD 50" Value Large Format Display



---

Seamless integration for great visual performance

Its thin bezel and super slim design perfectly complements today's modern surroundings whilst multiple display inputs support flexibility and freedom. With fixing points conveniently located on the back of the screen, external equipment can be attached with seamless simplicity. Reasonable brightness levels offer visibility in controlled light surroundings. The professional haze filter is allowing excellent readability. Landscape and portrait capability matches the needs of both corporate huddle spaces and retail signage applications. With a built-in media player, the NEC C Series runs content directly from a USB drive or microSDHC card as a standalone solution but can also download contents via network. Futureproof connectivity handles input from multiple sources. Don't let technology impact design – get seamless integration with the NEC C Series!

**Benefits**

- **FullHD LCD technology** – eye-pleasing black levels and impressive contrast ratios for ergonomic viewing and less fatigue in conferencing scenarios.
- **Modern and slim design** – robust yet elegant allowing for an unobtrusive integration into any application and environment.
- **All-in-one Signage solution integrated** – the integrated mediaplayer for simple signage use supports easy content playback and management.
- **Mission-critical 24/7 ready operation** – the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.
- **Ease of use and operation** – Smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.
- **Free Download of Multi-Display Management Software** – with NaViSet Administrator 2 you can manage all your connected display devices from a centralised location.

## Product information

Product Name	MultiSync® C501
Product Group	LCD 50" Value Large Format Display
Order Code	C501

### Display

Panel Technology	AMVA3 with Edge LED backlights
Active Screen Area (W x H) [mm]	1,095 x 616
Screen Size [inch/cm]	50 / 125.7
Brightness [cd/m <sup>2</sup> ]	400 (Normal Operation)
Contrast Ratio (typ.)	4000:1
Viewing Angle [°]	178° Vert., 178° Hor. @ CR>10
Colour Depth [bn]	1.073 (10bit)
Response Time (typ.) [ms]	6.5 (grey-to-grey)
Haze Level [%]	Pro (44)
Supported Orientation	Face Up; Landscape; Portrait; Face Down

### Synchronisation Rate

Horizontal Frequency [kHz]	15.625/15.734, 31.5 - 91.1
Vertical Frequency [Hz]	50.0 - 85.0 (Analog Input) / 24.0 - 85.0 (Digital Input)

### Resolution

Native Resolution	1920 x 1080
Supported Resolutions on HDMI and DisplayPort	1920x1080@60Hz; 1080p, 1080i, 720p@60/50Hz

### Connectivity

Input Video Analogue	1 x VGA; 1 x Composite (RCA)
Input Video Digital	1 x DisplayPort (with HDCP); 3 x HDMI (with HDCP)
Input Audio Analogue	2 x 3.5 mm jack
Input Audio Digital	1 x DisplayPort; 3 x HDMI
Input Control	1 x LAN 100Mbit; 1 x Remote Control (3.5 mm jack); 1 x RS232
Input Data	1 x microSD (MediaPlayer); 1 x USB 2.0 (MediaPlayer)
Output Audio Analogue	1 x 3.5 mm jack
Output Control	remote control wire (3.5mm jack)

### Sensors

Ambient Light Sensor	Integrated, triggered actions programmable
Temperature Sensor	Integrated, 3 sensors, triggered actions programmable

### Electrical

Power Consumption [W]	65 (Normal Operation)
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)
Power Management	VESA DPMS

### Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	20 to 80

**Mechanical**

Dimensions (W x H x D) [mm]	1,125 x 645 x 45
Weight [kg]	16.1
Bezel Width [mm]	12.4 (left and right); 12.4 (top and bottom)
VESA Mounting [mm]	300 x 300 (FDMI); 4 holes; M6
Ingress Protection	IP5X (front); IP2X (back)

**Additional Features**

Special Characteristics	Ambient Light Sensor; AMX NetLinX Support; ASCII Control Commands; Automated Email Alert; CEC Support; Crestron Connected Support; Crestron RoomView Support; Display Browser Control; Emergency Notification; Full System Scheduler; KeyGuide; MediaPlayer with Browser Control; NaViSet Administrator 2; OmniColor Control; OSD rotation for portrait mode; PJLink Support; Powered USB-Port; Removable Logo; Secure Mode Operation; Slim LED Indicator; SNMP Support; TileMatrix (10 x 10)
Colour Versions	Black Front Bezel, Black Back Cabinet
Safety and Ergonomics	CE; EMC Class B; FCC; PSB; RoHS; TÜV GS; UL/C-UL or CSA; VCCI
Audio	Integrated Speakers (10 W + 10 W)
Shipping Content	CD-ROM (User Guides/Manuals); Display; Power Cable; Remote Control; VGA cable
Warranty	3 years warranty incl. backlight; additional services available
Operating Hours	24/7

**Available Options**

Accessories	Wall mounts (LCM1U, RXF2, RXT2, LSM1U, LTM1U, MTMP1U, LTTU, TS525TU); Stand (ST-401)
-------------	--------------------------------------------------------------------------------------

**MediaPlayer**

Supported Image Formats	JPG (baseline, progressive, RGB, CMYK); max. resolution 5000 x 5000; PNG (interlace, alpha channel); max. resolution 4000 x 4000
Supported Video Formats	.mpg, .mpeg, .wmv, .mov, .flv, .f4v (H.264: 1080p@30fps/1080i@60fps; MP2: MP@ML, MP@HL)
Supported Audio Formats	.wav, .mp3 (Sampling up to 48kHz) (Bit rates: MP2 - Up to 384 kbps, MP3 - Up to 320 Kbps, ACC - Up to 1440 Kbps)
Supported File Storage / File System	MicroSDHC / FAT16, FAT32; USB 2.0 / FAT16, FAT32

**Green Features**

Energy Efficiency	Ambient light sensor; Annual energy consumption: 110 kWh (based on 4 operating hours per day); Carbon savings meter; Energy efficiency class: A
Ecological Materials	Manuals on CD; Optional feet
Ecological Standards	EnergyStar 7.0



For more information, visit [au.nec.com](http://au.nec.com), email [contactus@nec.com.au](mailto:contactus@nec.com.au) or call 131 632

**Corporate Headquarters (Japan)**  
 NEC Corporation  
[www.nec.com](http://www.nec.com)

**Australia**  
 NEC Australia Pty Ltd  
[au.nec.com](http://au.nec.com)

**North America (USA)**  
 NEC Corporation of America  
[www.necam.com](http://www.necam.com)

**Asia Pacific (AP)**  
 NEC Asia Pacific  
[sg.nec.com](http://sg.nec.com)

**Europe (EMEA)**  
 NEC Enterprise Solutions  
[www.nec-enterprise.com](http://www.nec-enterprise.com)

v.14.02.18 | C501

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

©2018 NEC Australia Pty Ltd. All rights reserved. NEC and NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.

