

Product Information Sheet

X651UHD-2 65" Ultra-High Definition Large Format



Unmatched richness of detail

Enjoy a new era of visual experience with an expansive digital canvas delivering pixel-free viewing. This 65 inch (164 cm) Ultra High Definition (UHD) screen is perfectly suited for reference applications and smaller workgroups up to 6 people where intense detail and colour accuracy is demanded. The 3840 x 2160 resolution facilitates both distance and proximity viewing with precise colour fidelity regardless of the viewing angle for a reality-like visual experience. Designed for 24/7 operation and offering high usage flexibility thanks to its wide connectivity, this screen provides future-proof investment security.

This state-of-the-art technology is ideal for any heavy duty applications including professional conferencing, CAD/CAM, creative multimedia design, control room, medical review as well as high end retail signage applications.

Benefits

- **Stunning "pixel-free" ergonomic viewing** – delivered by an Ultra High Definition (3,840 x 2,160) Professional LED backlit S-IPS panel.
- **Enhanced imaging performance** – advanced settings of all relevant visual parameters allow full control of brightness, colour, gamma and uniformity via the Spectraview Engine for precise, natural images.
- **Reliable colour reproduction** – due to 10-bit colour performance, extreme viewing angles and hardware calibratable LUT, viewers benefit from consistently accurate image rendering.
- **Mission-critical 24/7 ready operation** – with reliable, industry grade components and NEC trusted performance.
- **Wide array of flexible application scenarios** – thanks to multi-source conferencing and efficient split-screen operation supported by a wide futureready range of digital connectivity.
- **Future Ready with OPS Cable Free Expansion** – upgrade the power of your display at any time while seamlessly integrating one of our various Slot-in PCs, signal interfaces and other OPS compatible products without the need for external cables or devices.
- **Perfectly Scaled** – lower resolution content (e.g. FullHD) can be upscaled to UHD resolution via a bi-cubic 4x4 pixel interpolation algorithm in order to achieve smooth colours and clear edges.
- **Free Download of Multi-Display Management Software** – with NaViSet Administrator 2 you can manage all your connected display devices from a centralised location.

Product Information

Product Information

Product Name	X651UHD-2
Product Group	LCD 65" Ultra-High Definition Large Format Display
Order Code	X651UHD-2

Display

Panel Technology	S-IPS with Edge LED backlights
Active Screen Area (W x H) [mm]	1,428 x 804
Screen Size [inch/cm]	65 / 165
Brightness [cd/m²]	450, 270 Eco (shipment setting)
Contrast Ratio (typ.)	1300:1
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	8 (grey-to-grey)
Haze Level [%]	10
Supported Orientation	Face Up; Landscape; Portrait

Synchronisation Rate

Horizontal Frequency [kHz]	28 - 134
Vertical Frequency [Hz]	23 - 85

Resolution

Native Resolution	3840 x 2160 at 60 Hz
Supported on DisplayPort and HDMI	3840 x 2160 (24/30 Hz); 1920 x 1080; 1600 x 1200; 1360 x 768; 1280 x 1024; 1280 x 768; 1080i; 1080p; 1024 x 768; 800 x 600; 720p (50/60 Hz); 640 x 480; 480p (60 Hz)
Supported on DisplayPort only	3840 x 2160 (60 Hz)
Supported on HDMI only	4096 x 2160 (24 Hz); 3840 x 2160 (25 Hz); 1360 x 768; 576i (50 Hz); 480i (60 Hz)

Connectivity

Input Video Digital	1 x DisplayPort (with HDCP); 2 x DVI-D (with HDCP); 4 x HDMI (with HDCP)
Input Audio Analogue	1 x 3,5 mm jack
Input Audio Digital	1 x HDMI; DisplayPort
Input Control	LAN 100Mbit; remote control wire (3,5mm jack); RS232
Output Audio Analogue	3,5mm jack
Output Control	LAN 100Mbit
Remote Control	LAN with SNMP; Remote Control IR (internal/external (optional) sensor); RS-232C (9-pin D-sub) Input

Open Modular Intelligence

OPS Slot	Slot Technology: Open pluggable specification (NEC / Intel OPS standard)
Inrush Current [A]	max. 10
Power Consumption [W]	max. 61
Voltage / Current [V/A]	16/4

Sensors

Ambient Light Sensor	Integrated, triggered actions programmable
Human Sensor	Optional, external, 4-5m range, triggered actions programmable
Temperature Sensor	Integrated, 3 sensors, triggered actions programmable
NFC Sensor	Integrated, 2cm range, free NEC Android App required

X651UHD-2 LCD 65" Ultra-High Definition Large Format Display

Electrical

Power Consumption [W]	150 Eco (shipment setting), 200
Power Savings Mode [W]	< 0.5; < 0.5 (ECO Standby)
Power Management	VESA DPMS

Environmental Conditions

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	20 to 80

Mechanical

Dimensions (W x H x D) [mm]	Without stand: 1,468 x 844 x 87
Weight [kg]	Without stand: 41
Bezel Width [mm]	17.5; 17.5 bottom/right; 17.5 top/left
VESA Mounting [mm]	4 holes; 400 x 400 (FDMI); M8
Ingress Protection	IP40 (front); IP20 (back)

Additional Features

Special Characteristics	Carbon footprint meter; DICOM support; NaViSet Administrator 2
Colour Versions	Black Front Bezel, Black Back Cabinet
Safety and Ergonomics	C-tick; CE; FCC Class B; PSB; RoHS; TÜV GS; UL/C-UL or CSA; VCCI
Audio	Integrated Speakers (10 W + 10 W); Optional Speakers (15 W + 15 W)
Shipping Content	CD-ROM (User Guides/Manuals); Display; DisplayPort Cable; Power Cable; Remote Control
Warranty	3 years Conditional Warranty
Operating Hours	24/7

Available Options

Accessories	Wall Mount (LSM1U,LTM1U,LTAPU,RXF2 & RXT2). Stand ST-4620
OPS Slot	HD-SDI 3G; HDBaseT receiver; Intel® Atom, Celeron and Core CPUs; OPS-2C HDMI + DP Interface; OPS-2C Quad 3G SDI

Green Features

Energy Efficiency	Ambient light sensor; Annual energy consumption: 222 kWh (based on 4 operating hours per day); Carbon savings meter; ECOMode; Energy efficiency class: A; Human Sensor
Ecological Materials	Manuals on CD; Optional feet

For more information, visit au.nec.com, email contactus@nec.com.au or call 131 632

Corporate Headquarters (Japan)
NEC Corporation
www.nec.com

Australia
NEC Australia Pty Ltd
au.nec.com

North America (USA)
NEC Corporation of America
www.necam.com

Asia Pacific (AP)
NEC Asia Pacific
sg.nec.com

Europe (EMEA)
NEC Enterprise Solutions
www.nec-enterprise.com

v.06.12.17 | X651UHD-2

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

© 2017 NEC Australia Pty Ltd. All rights reserved. NEC and NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.

NEC