

### Product Information Sheet

# CB851Q - 85" Collaboration Board





# Enter a world of interactive white-boarding

Upgrade your lectures and meetings with NEC's all-in-one collaboration boards, in three different sizes, featuring UHD resolution and up to 20 touch points. Based on infrared touch technology the user experiences perfect usability with a rapid touch response. Business and educational sessions start-up instantly with built-in whiteboard and wireless screen sharing functionalities without any hidden costs. The embedded annotation tool lets you annotate over any content shown on the screen.

For more demanding applications, the OPS slot provides the opportunity to enhance the computing power. With sizes including 65", 75" and 86", the NEC CB Series offers the ideal solution for your meeting and class rooms.

All NEC CB Series displays come with three magnetic pens and a wall-mount fitting for easy installation.

#### Benefits

Out-of-the-box collaboration – thanks to embedded computing with built-in annotation tools and wireless presentation capabilities.

Multi-Touch - true multi-touch support with up to 20 simultaneous touch points.

**Protective Glass** – premium toughened glass protects the security of the panel yet delivers a perfect touch experience with anti-glare coating to minimise reflections and fingerprints.

Simple operation – with easy front access to USB ports and controls for major functionalities

Ease of Use – enhance the display with an optional "Windows based" Slot-in-PC using the integrated Ultra High Resolution OPS option slot, thereby simplifying installations and reducing the points of failure.

**Cost Saving Device Management** – save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.



Product information	
Product Name	MultiSync® CB861Q (Infrared Touch)
Product Group	LCD 86" Ultra-High Definition Large Format Touch Display
Order Code	CB851Q
Display	
Panel Technology	IPS with Direct LED backlights
Active Screen Area (W x H) [mm]	1,895 x 1,066
Screen Size [inch/cm]	86 / 217.4
Aspect Ratio	16:9
Pixel Pitch [mm]	0.4935
Brightness [cd/m²]	350, 300 (shipment setting)
Contrast Ratio (typ.)	1200:1
Viewing Angle [°]	178 / 178 (at contrast ratio > 10:1)
Colour Depth [bn]	1,073 (10bit)
Response Time (typ.) [ms]	8 (grey-to-grey)
Haze Level [%]	3
Supported Orientation	Landscape
Synchronisation Rate Horizontal Frequency [kHz]	26 - 135
Vertical Frequency [Hz]	23 - 80
Resolution	
Native Resolution	3840 x 2160
Supported Resolutions	4096 x 2016; 3840 x 2160; 1920 x 1080
Supported on HDMI only	4096 x 2016 (24 Hz); 3840 x 2160 (60 Hz)
Connectivity	
Input Video Analogue	1 x VGA
Input Video Digital	3 x HDMI (with HDCP)
Input Audio Analogue	1 x 3,5 mm jack
Input Audio Digital	3 x HDMI
Input Control	LAN 100Mbit; RS232
Input Data	2 x USB Type-B (Upstream); 6 x USB 2.0 (Downstream)
Output Audio Analogue	1 x 3,5 mm jack
Output Audio Digital	1 x SPDIF
Output Control	LAN 100Mbit
Open Modular Intellige	nce
OPS Slot	Slot Technology: Open pluggable specification (NEC / Intel OPS standard)



<b>Electrical</b>	
LICCUITCAI	

Power Consumption Eco/max.	365 Eco (shipment setting), 620
[W]	
Power Savings Mode [W]	< 0.5; < 2 (Networked Standby)

#### **Environmental Conditions**

Operating Temperature [°C]	+0 to +40
Operating Humidity [%]	10 to 90

#### Mechanical

Dimensions (W x H x D) [mm]	Without stand: 1,957.1 x 1,159.8 x 86.8
Weight [kg]	Without stand: 67.3
Bezel Width [mm]	18 (left, right and top); 45 (bottom)
VESA Mounting [mm]	4 holes; 800 x 600 (FDMI); M8

#### Glass

Thickness [mm]	4
Туре	Thermal-tempered, anti-glare coating
Light Transmission [%]	88 (+/- 1 %)
Reflection Rate [%]	4
Hardness [H]	7

#### Touch

Touch Technology	Infrared Touch
Number of Touches	Real multi-touch up to 20 touches
Touch Method	Finger; Gloves; Stylus (≥ 8 mm)
Supported Operating System	Native Multi-Touch: Windows 7, Windows 8, Windows 10, Linux, Android; Default Mouse: Windows XP, Windows Vista, Mac OS X
Data Interface	USB-HID
Accuracy [mm]	< 2

# **Embedded Computing**

Built-in Applications	File Manager; Input Select; Setting; Web Browser; Whiteboard - Mosaic Canvas; Wireless Presentatiom - Mosaic Connect
System Memory	2G RAM
Internal Storage	16GB ROM

## **Available Options**

Accessories	NP05LM4 Wireless LAN Module
OPS Slot	Intel (R) Celeron and Core CPU OPS PC's

## **Green Features**

CB851Q | NEC Australia | nec.com.au

#### **Additional Features**

Special Characteristics	AMX NetLinx Support; Crestron Connected Support; Crestron RoomView Support; DICOM Simulation; HDMI with UHD at 60 Hz; NaViSet Administrator 2; Scheduler
Colour Versions	Black Front Bezel, Black Back Cabinet
Safety and Ergonomics	BSMI; CE; EAC; EMC Class B; FCC; PSB; RCM; REACH; RoHS; SASO; UL/C-UL
Audio	Integrated Speakers (2 x 12 W)
Shipping Content	$3 \times \text{Stylus}$ ; HDMI Cable; Power Cable; Remote Control; USB cable; User Manual; VGA cable; Wall Mount
Warranty	3 years warranty incl. backlight
Operating Hours	12/7







#### For more information:



nec.com.au



contactus@nec.com.au



131 632

**Corporate Headquarters (Japan)**NEC Corporation www.nec.com

**Australia** NEC Australia Pty Ltd www.nec.com.au

North America (USA) NEC Corporation of America www.necam.com

Asia Pacific (AP) NEC Asia Pacific www.sg.nec.com

**Europe (EMEA)**NEC Enterprise Solutions
www.nec-enterprise.com

v.19.09.17 | CB851Q

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

