

Product Information Sheet

EA245WMi-2 - LCD 24" Commercial Display



NEC MultiSync® EA245WMi-2 Ultra-Thin Bezel - The Office benchmark, combining sleek and elegant design with health-conscious performance

The 24" ultra-thin bezel display targeting ultimate office productivity, performance and quality, fulfils the demand for future-ready design. With its full height adjustability from 0 to 150 mm and 170° swivel functionality this display ensures perfect individual ergonomic set-up supporting best productivity. Ensuring the well-being of the user, built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates the effect of flickering. The users' eyes are protected whilst ensuring a true-to-life display colour performance from all viewing angles. The LED backlight panel with AH-IPS technology supports a high display brightness of 300 cd/m² and in parallel lowers power consumption.

The ultra-narrow bezel display reduces the display footprint without compromising on screen size and gives an office a fresh professional interior with its sleek and elegant design.

Benefits

Ergonomic Office – full height adjustability (150 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.

Protecting your eyes from strain and damage – Built-in Low Blue Light technology filters out hazardous blue light emissions whilst Flicker-Free technology eliminates any backlight flickering, thus protecting your eyes against cataracts and macular degeneration without compromise to true-to-life display colour performance.

Highest Productivity and efficient Multi-Tasking – reduce the number of PCs and Daisy-Chain multiple displays using DisplayPort (out) and benefit from Uniformity Control for a consistent visualisation in a trading floor setup.

Auto-Adjust Power Consumption – to minimize unnecessary power usage, the Human and Ambient Light Sensors adjust

the display brightness according to user presence and room lighting conditions.

Future-Ready Design – best in form and function design with 3-sided ultra-narrow bezel gives an office a fresh professional interior.

Business Class Image Quality – Advanced High-Performance IPS (AH-IPS) panel provides the very best viewing angles as well as noticeably better colour reproduction.

Product information

Product Name	MultiSync® EA245Wmi-2
Product Group	LCD 24" Commercial Display
Order Code	EA245Wmi-2-BK

Display

Panel Technology	IPS TFT with W-LED backlight
Screen Size [inch/cm]	24 / 61
Screen Aspect Ratio	16:10
Pixel Pitch [mm]	0.270
Brightness (typ.) [cd/m²]	300
Contrast Ratio (typ.)	1000:1 (5000:1 dynamic contrast ratio)
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	5
Colours [Mio.]	16.77

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 95
Vertical Frequency [Hz]	56 - 75

Resolution

Optimum Resolution	1920 x 1200 at 60 Hz			
Supported	1920 x 1200;	1440 x 900;	1280 x 1024;	1024 x 768;
	1920 x 1080;	1400 x 1050;	1280 x 960;	800 x 600;
	1680 x 1050;	1366 x 768;	1280 x 768;	640 x 480
	1600 x 1200;	1360 x 768;	1280 x 720;	

Connectivity

Digital	1 x DisplayPort; 1 x DisplayPort out; 1 x DVI-D; 1 x HDMI; USB ver. 3.0 (3 down / 1 up)
Analog	1 x D-sub 15 pin

Electrical

Power Consumption on Mode [W]	18 (Eco Mode 2); 22 (typ.); 50 (max.)
Power Savings Mode [W]	0.3
Power Supply	internal power supply

Environmental Conditions

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80

Ergonomics

Height adjustable stand [mm]	150
Screen Tilt / Swivel [°]	-5 to +35; -170 to +170
Screen Rotate [°]	-90 to 90 (landscape to portrait mode)

Mechanical

Bezel Width [mm]	0.8 (left/right/top)
Dimensions (W x H x D) [mm]	With stand: 531.5 x 515.4 x 250
Weight [kg]	6.7
VESA Mounting [mm]	100 x 100

Additional Features

Special Characteristics	Ambient light sensor for optimized brightness levels; Carbon Footprint Meter; Carbon Savings Meter; ControlSync®; Customize Setting; DICOM preset; DICOM Simulation; EcoModes; Human Sensor; LED Backlight Technology; NaViSet Administrator 2; Quick release Stand and Handle; sRGB Support; Touch Sensor Keys; USB ver. 3.0 (3 down / 1 up)
Colour Versions	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
Cable Management	yes
Kensington security slot	yes
Plug and Play	VESA DDC2B; VESA DDCi
Audio	Headphone Jack; Integrated Speakers (1 W + 1 W)
Adjust Functions	Audio Volume / Lock-Out; Auto Adjust; Brightness; Colour Temperature Control; Contrast; Control Sync; DV Mode; EcoMode; Fine Adjust (analog); Human Sensing; Intelligent Power Management; Language Select; LED Brightness; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; One Touch Recovery; Power-Off Timer; sRGB
Shipping Content	Control Sync Cable; DisplayPort cable; Monitor; Power Cable; Setup Guide; USB Cable
Safety and Ergonomics	CE; EnergyStar 7.0; Flicker-free; Low Blue Light; TCO 7.0 ; CRM
Warranty	3 years at 16/7 usage warranty

Green Features

Energy Efficiency	Ambient light sensor; Annual energy consumption: 31 kWh (based on 4 operating hours per day); Energy efficiency class: A+; Human sensor; Intelligent Power Management
Ecological Materials	Downloadable manuals
Ecological Standards	Energy Star 7.0; TCO 7.0



CE

For more information:

 nec.com.au
 contactus@nec.com.au
 131 632

Corporate Headquarters (Japan)
 NEC Corporation
www.nec.com

Australia
 NEC Australia Pty Ltd
www.nec.com.au

North America (USA)
 NEC Corporation of America
www.necam.com

Asia Pacific (AP)
 NEC Asia Pacific
www.sg.nec.com

Europe (EMEA)
 NEC Enterprise Solutions
www.nec-enterprise.com

v.20.06.03 | EA245WMi-2-BK

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

©2020 NEC Australia Pty Ltd. All rights reserved. NEC and NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.

