

Product Information Sheet

EA271U - LCD 27" Commercial Display



Outstanding pixel-free visualisation with future-proof professional office productivity

Where highest detail display quality is of the utmost importance, only 4K UHD resolutions can provide the perfect tool for the job. This 27" ultra-narrow bezel display delivers peak performance and visualisation with up to 3840 x 2160 pixels for superior productivity for professionals.

With high attention to user well-being, this display offers outstanding ergonomic features for an individually tailored workspace. Furthermore, with an integrated ambient light sensor, Low Blue Light and Flicker-Free technology, the user can maintain high productivity without risk to eyes. Maintain focus with a decluttered desk; with Type-C connectivity, just a single cable manages video, audio, power and USB. Excellence in future-proof connectivity ensures investment protection and peace of mind.

This display is perfectly positioned to meet the demanding pixel-free visualisation needs of content creators (photo, video, cinema, and movies), CAD/CAM designers as well as control room and trading floor operators.

Benefits

Deliver highest display quality – optimize your workflow by displaying bigger spreadsheets, clearer text, extended data, more lines of code and life-like images thanks to 4K UHD resolutions with up to 3840x2160 pixels.

Newest USB Type-C connectivity standard – optimize connectivity and declutter your desk; replace video, audio, power and USB cabling with just a single cable to connect your notebook/tablet PC with the display.

Maximum attention to health and well-being – the outstanding ergonomic height adjustment from 0 to 150 mm; eye pleasing built-in Low Blue Light and Flicker-Free technology; plus integrated ambient light sensor all combines to tailor the perfect individual setup to boost productivity.

Best in form and function – future-ready design with 3-sided ultra-narrow bezel, complementing a fresh professional office interior.

Auto-Adjust Power Consumption – to minimize unnecessary power usage, the Human and Ambient Light Sensors adjust the display brightness according to user presence and room lighting conditions.

Ease of multi-display control – manage the settings of up to 8 displays in a multi-monitor configuration via the master display with ControlSync® technology.

Product information

Product Name	MultiSync® EA271U
Product Group	LCD 27" Commercial Display
Order Code	EA271U-BK

Display

Panel Technology	IPS TFT with W-LED backlight
Screen Size [inch/cm]	27 / 68
Screen Aspect Ratio	16:9
Colour Gamuts	110 % sRGB; 81.6% AdobeRGB, 78% NTSC
Pixel Pitch [mm]	0.155
Brightness (typ.) [cd/m²]	350
Contrast Ratio (typ.)	1300:1 (9000:1 dynamic contrast ratio)
Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
Response Time (typ.) [ms]	5
Colours [Mio.]	1064.64332261

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 135
Vertical Frequency [Hz]	30 - 75

Resolution

Optimum Resolution	3840 x 2160 at 60 Hz			
Supported	3840 x 2160; 2560 x 1440; 1920 x 1440;	1920 x 1080; 1600 x 1200; 1280 x 1024;	1152 x 864; 1024 x 768; 832 x 624;	800 x 600; 640 x 480

Connectivity

Digital	1 x DisplayPort; 1 x USB Type C (60 W); 2 x HDMI; USB ver. 3.1 (3 down / 1 up)
---------	--

Electrical

Power Consumption on Mode [W]	150 (max.); 30 (Eco Mode 1); 38 (Eco Mode 2); 38 (shipping)
Power Savings Mode [W]	0.33
Power Supply	1.6 A/0.75 A; 100-240 V; integrated power supply

Environmental Conditions

Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
Storage Humidity [%]	10 to 85
Storage Temperature [°C]	-10 to 60

Ergonomics

Height adjustable stand [mm]	150 (Landscape mode)
Screen Tilt [°]	-5 to 35
Screen Swivel [°]	-170 to +170
Screen Rotate [°]	-90 to 90 (landscape to portrait mode)

Mechanical

Bezel Width [mm]	1 (left and right); 1 (top)
Dimensions (W x H x D) [mm]	361.9 x 628.6 - 652.1 x 250 (Portrait mode); 611.8 x 378 - 528 x 250 (Landscape mode)
Weight [kg]	With stand: 9.5; Without stand: 6.1
VESA Mounting [mm]	100 x 100

Additional Features

Special Characteristics	Advanced NTAA; Ambient light sensor for optimized brightness levels; ControlSync®; Customize Setting; DDC/CI compatible; DICOM Simulation; EcoModes; ErgoDesign®: Height adjustable stand (150 mm) with 90° Pivot features; Human Sensor; LED Backlight Technology; Picture-by-Picture; Quick release Stand and Handle; Versatile and easy installation (VESA standard) with NaViSet and NaViKey
Colour Versions	Black Front Bezel, Black Back Cabinet;
Cable Management	yes
Kensington security slot	yes
Plug and Play	EDID Standard; VESA DDC2Bi; VESA DDCi
Audio	1W + 1W (De-activateable); Headphone Jack
Adjust Functions	DV Mode; EcoMode; Human Sensing; Intelligent Power Management; sRGB
Shipping Content	Control Sync Cable; Display; DisplayPort cable; Power Cable; Set-up manual; USB Cable
Safety and Ergonomics	CE; EAC; ErP; Flicker-free; ISO 9241-307 (pixel failure class I); PSB; RoHS; TÜV Ergonomics; TÜV GS; UL/C-UL or CSA
Warranty	3 years warranty incl. backlight; optional 4th to 5th year warranty extension

Green Features

Energy Efficiency	Ambient light sensor; Carbon Footprint Meter / Carbon Savings Meter; ECOMode; Energy efficiency class: A; Human sensor; LED backlight technology
Ecological Materials	Minimal use of harmful material
Ecological Standards	Energy Star 7.1; ErP compliant; RoHS compliant; TCO 7.0



CE



ErP



RoHS

TÜV
Ergonomics

TÜV GS

For more information:

nec.com.au

contactus@nec.com.au

131 632

Corporate Headquarters (Japan)
NEC Corporation
www.nec.com

Australia
NEC Australia Pty Ltd
www.nec.com.au

North America (USA)
NEC Corporation of America
www.necam.com

Asia Pacific (AP)
NEC Asia Pacific
www.sg.nec.com

Europe (EMEA)
NEC Enterprise Solutions
www.nec-enterprise.com

v.26.06.20 | EA271U-BK

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

©2020 NEC Australia Pty Ltd. All rights reserved. NEC and NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.