# Product Information Sheet Indoor LED 1.56 mm Black Face LED Panel

# NEC E-Series - LED-E015I



# Essential bundles of brilliance

For bezel-free viewing experiences using vivid LED technology, NEC's LED Solution delivers essential visualization for scalable large digital surfaces. Even for cost-conscious deployments for presentation and signage, NEC's LED Solution provides long lasting NEC quality with industrial-grade power supplies in easy to install.

The entry-level NEC E Series provides cost conscience customers impressive LED imaging without compromising on the service and support expected from the NEC brand. The front serviceable design allows easy access and quick maintenance when needed. Boardrooms, auditoriums, retail, and education are just some of the applications where the NEC E series is designed to be integrated. The front serviceable design allows easy access and quick maintenance when needed. NEC offers full planning and design, installation and post installation maintenance support, ensuring you get a custom tailored solution allowing you to focus on what's most important – your business.

## Benefits

Care-free installation - with bundled solutions that deliver all you need to get your LED video wall up and running.

Large scale for perfectly detailed imagery - completely bezel-less design with high contrast rates deliver an unhindered

viewing experience.

Slim design – with a flush rear profile, LED modules can be integrated very close to the wall with no gap necessary due to minimal heat emission.

Front serviceable modules – with front access to the LED modules, maintenance is easy.

Visual excellence – high contrast and high brightness is inherent in LED delivery, benefit from NEC's long lasting quality.



| Product information |                              |
|---------------------|------------------------------|
| Product Name        | LED-E015I                    |
| Product Group       | Indoor LED 1.56 mm LED panel |

## Display

| Pixel Configuration       | 3-in-1 SMD (Black)            |
|---------------------------|-------------------------------|
| LED type                  | SMD                           |
| Panel Size [mm]           | 600x337.5                     |
| Aspect Ratio              | 16:9                          |
| Pixel Pitch [mm]          | 1.56                          |
| Brightness (max.) [cd/m²] | 600                           |
| Lifetime                  | 100000 hrs (50% brightness)   |
| Contrast Ratio (typ.)     | 7000:1                        |
| Viewing Angle [°]         | 160 horizontal / 160 vertical |
| Dimming Capability        | 256 levels                    |
| Colour Processing         | l6 bit                        |
| Colours                   | 281 trillion                  |
| LED Driving Method        | I/30 dynamic scan             |
| Frame Rate                | 50/60 Hz                      |
| Refresh Rate [Hz]         | < 3840                        |
| Colour Temperature [K]    | 2500 - 1000                   |
|                           |                               |

#### **Screen Resolution**

| Resolution                          | 384 x 216 |
|-------------------------------------|-----------|
| Resolution per m <sup>2</sup>       | 230,400   |
| Number of Pixel per module<br>[dot] | 192 x 108 |
| Number of Pixel per card<br>[dot]   | 46,625    |

## Connectivity

| Input Video Digital | Novastar         |
|---------------------|------------------|
| Input Control       | Gigabit Ethernet |

## Electrical

| Total Power Consumption [W] | 40 typ. / 125 max.      |
|-----------------------------|-------------------------|
| Power Consumption typ. [W]  | 197 per m² (normal use) |
| Power Consumption max. [W]  | 617 per m <sup>2</sup>  |

## **Environmental Conditions**

| Operating Temperature [°C] | -10 to 40 |
|----------------------------|-----------|
| Operating Humidity [%]     | 10 to 80  |

#### Mechanical

| Dimensions (W x H x D) [mm]               | 600 x 337.5 x 29 |
|---|------------------|
| Dimensions (W x H x D) [mm]<br>per module | 300 × 168.75 × 8 |
| -   |                  |

| Weight [kg] | 4.7 |
|-------------|-----|
|             |     |

#### Additional Features

| Shipping Content | LED Controller; LED Modules; Pixel Card Removal Tool; Spare Parts Kit |  |
|------------------|---|--|
| Manufacturer     | NEC   |  |
| Serviceability   | Front Service   |  |
| IP Level         | IP20  |  |
| Certifications   | RCM   |  |
| Warranty         | 3 years conditional warranty  |  |
|                  |   |  |

#### For more information:

www nec.com.au

contactus@nec.com.au

131 632

Corporate Headquarters (Japan) NEC Corporation www.nec.com

v.12.07.21 | LED-E015I

Australia NEC Australia Pty Ltd www.nec.com.au North America (USA) NEC Corporation of America www.necam.com Asia Pacific (AP) NEC Asia Pacific www.sg.nec.com Europe (EMEA) NEC Enterprise Solutions www.nec-enterprise.com

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

©2021 NEC Australia Pty Ltd. All rights reserved. NEC and NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.

