

NEC NC2402ML Laser Projector

Datasheet



Modular Cinema Projection - a new standard in adaptable screening

The world's first cinema projector offering a modular laser light system with projector head, all in one box. The modular concept allows you to plug-in the appropriate light modules based on the brightness you need. Protect your investment when migrating from 2D to 3D projection, or adapting your set-up to a wider screen.

The NC2402ML utilises RB laser technology which is almost speckle-free compared to RGB technology, providing similar benefits yet at a lower cost. Don't limit your venue's potential; go beyond cinema to increase your visitor numbers and maximise revenue. The modular light concept opens opportunities to screen alternative content for corporate presentations and gaming events.

You can expect a powerful modular projector that delivers compelling advantages when it comes to operation, efficiency and image quality. Ideally operating in medium-sized venues and with premium format cinema screens of up to 22m.

Benefits

Modular Light Source - achieve the light output which is perfectly adjusted to your requirements with exchangeable light modules 24,500lm, 20,000lm and 18,000lm for different brightness demands.

Virtually zero maintenance - no lamp and no filter replacement costs, no maintenance personnel costs and no lamp stock due to the innovative Laser Light engine.

Enjoy a Lower TCO - highest reliability, maintenance-free operation, low power consumption and up to 50000 hours life; the Laser light source results in a significantly lower total cost of ownership.

Sealed optical engine - minimising dust ingress, consistent performance is assured and no special maintenance is required.

A host of integrated features - including built-in 2TB screen server, 2 x 3G SDI Interfaces, HDMI interface for alternative content, advanced network and built-in GPIO functions with NAS support.

Product Information

Product Name	NEC NC2402ML
Product Group	Laser Projector
Components	Projector Head NP-02HD (60004880), Laser Light Source NP-24LU01 (100015207)
Order Code	NP-NC2402ML

Optical

Projection Method	3-chip DLP Cinema® Technology
Screen Size [m]	up to 22 in DCI colour (1.8 Gain screen)
Brightness	Up to 24500 Lumen
Contrast Ratio	2000:1
Light Source	Laser Light Source, expected life: up to 50000 h ¹
Lens	Zoom / Focus / Shift: Motorized Other: Range of shift is dependent on lens Primary Lenses: NC-60LS12Z:1.2-1.81:1; NC-60LS14Z:1.4-2.05:1; NC-60LS16Z:1.59-2.53:1; NC-60LS19Z:1.9-3.25:1; NC-60LS24Z:2.4-3.9:1; NC-60LS39Z:3.9-6.52:1
DMD Specifications	2048 x 1080 Chip: 0.98" S2K, DLP Cinema® Technology
Cooling Method	Circulating air cooling system Liquid: Cooling inside, no chiller required

Connectivity Projector

External Controls	1 x D-Sub 9 pin (RS-232); 1 x GPIO (3D) (D-sub 15 pin female); 1 x GPIO (D-sub 37 pin female); 1 x RJ45 100Base-T; 1 x USB port (TypeA)
-------------------	---

Environmental Conditions

Operating Temperature [°C]	10 to 35
Operating Humidity [%]	10 to 85 - non-condensing
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	10 to 85 - non-condensing

Electrical

Power Supply	Built-in power supply Projector Power Supply Unit: 200 to 240V AC, 50/60Hz, single phase
Rated Input Current	Projector power: 18.1A @ 200V-240V
Power Consumption [W]	3070 max.
Heat Dissipation (BTU)	10475

Mechanical

External Dimensions (W x H x D) [mm]	697 x 509.5 x 1,337
Weight [kg]	150 (without lens)
Fan Noise [dB (A)]	< 50

Additional Features

Special Characteristics	Built-in IMS (IMS3000, optional); Compact model; Dust sealed optical engine; Laser Light System; Latest digital technology; Low TCO; Metal filter; RB laser light source; Reduced costs
-------------------------	---

Green Features

Ecological Materials	Laser technology reduces power usage and reduces replacement materials required
----------------------	---

Interfaces: Dolby IMS3000 (optional)

External Controls	2 x RJ45 (4 GPI and 6 GPO); 3 x RJ45 Gigabit Ethernet
Input Terminals	1 x USB Type 2.0; 2 x 3GSDI bidirectional (input and output); 2 x USB Type 3.0; eSATA; HDMI
Output Terminals	2 x RJ45 (16-channel AES3-EBU Digital Audio)
Additional Features	HFR 3D Support (48 Hz/eye, 60 Hz/eye); Integrated SMS; Integrated Storage: 2 TB (DCP, RAID5); NAS support

Warranty

Warranty	2 years, parts warranty
Light Source	2 years or 7500h (whatever comes first)

¹ 50% of initial brightness at the end of specified laser life time at 25 degree ambient temperature, under normal usage condition, not covered by standard warranty

This product has been equipped with a laser module and is classified as Class1 of IEC60825-1 Ed3 2014 and is classified as RG3 of IEC62471-5 Ed1 2015.

DO NOT LOOK DIRECTLY INTO THE BEAM.

NEC Australia Pty. Ltd. reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty. Ltd. and shall not be reproduced without prior written approval from NEC Australia Pty. Ltd.

©2021 NEC Australia Pty. Ltd. All rights reserved. NEC and NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.10.2021