Product Information Sheet Outdoor 8 mm LED Panel

LED-PRO-E 080







NEC Outdoor LED – Stunning Visibility in a bright world

For bezel-free viewing experiences using vivid LED technology, NEC's LED Solution delivers essential visualization for scalable large digital surfaces. Even for cost-conscious deployments for presentation and signage, NEC's LED Solution provides long lasting NEC quality with industrial-grade power supplies in easy to install.

NEC's innovative PRO-E SMD series generates crisp, clear viewing without fading or distortion in any ambient light, whether it's day or night, bright or dark.

Benefit from excellent viewing angles, consistent vibrant colours, superb brightness and long lasting performance for high impact display projects.

Benefits

Care-free installation – Low weight aluminium framed solution that reduces support structure loading for a more cost effective

project.

Large scale for perfectly detailed imagery – completely bezel-less design with high contrast rates deliver an unhindered

viewing experience.

Slim design – with a flush rear profile, LED modules can be integrated very close to the wall with no gap necessary due to minimal heat emission.

Front serviceable modules - with front access to the LED modules, maintenance is easy.

Visual excellence – high contrast and high brightness is inherent in LED delivery, benefit from NEC's long lasting quality.



Product information	
Product Code	LED-PRO-E 080
Product Group	Outdoor LED 8.0 mm LED panel

Display

3-in I SMD
SMD (2727)
960 × 960
1:1
8.0
5000
100000 hrs (50% brightness)
5000:1
140 horizontal / 120 vertical
256 levels
14 bit
4.4 trillion
I/5 dynamic scan
50/60 Hz
< 3840
2500 - 10000

Screen Resolution

Resolution	120 × 120
Resolution per m ²	15,625
Number of Pixel per module [dot]	40 × 40
Number of Pixel per card [dot]	14,400

Connectivity

Input Video Digital	I x HDMI 2.0; I x DP I.2; I x DVI-D
Input Control	I x GenLock; I x LAN; I x USB IN; I x USB OUT (Cascading)

Electrical

Total Power Consumption [W]	260 typ. / 780 max.
Power Consumption typ. [W]	282 per m² (normal use)
Power Consumption max. [W]	846 per m ²

Environmental Conditions

Operating Temperature [°C]	-40 to 80
Operating Humidity [%]	10 to 80

Mechanical

Warranty

Dimensions (W x H x D) [mm]	960 × 960 × 108
Dimensions (W x H x D) [mm] per module	320 x 320 x 42
Weight [kg]	38
Additional Features	
Shipping Content	LED Controller; LED Modules; Pixel Card Removal Tool; Spare Parts Kit
Manufacturer	NEC
Serviceability	Front & Rear Service
IP Level	IP65/IP65
Certifications	CCC; CE; FCC Class B; RoHS;RCM

For more information:

www nec.com.au

(lanan)

contactus@nec.com.au

3 years conditional warranty



Corporate Headquarters (Japan) NEC Corporation www.nec.com

v.30.09.21 | LED-PRO-E 080

Australia NEC Australia Pty Ltd

www.nec.com.au

North America (USA) NEC Corporation of America

Asia Pacific (AP) NEC Asia Pacific www.sg.nec.com Europe (EMEA) NEC Enterprise Solutions www.nec-enterprise.com

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

www.necam.com

©2021 NEC Australia Pty Ltd. All rights reserved. NEC and NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.

