

Product Information Sheet Indoor LED 1.86 mm Black Face LED Panel

LED-N-018





Quality, Performance and Service

For bezel-free viewing experiences using vivid LED technology, NEC's LED Solution delivers essential visualization for scalable large digital surfaces. Even for cost-conscious deployments for presentation and signage, NEC's LED Solution provides long lasting NEC quality with industrial-grade power supplies in easy to install.

The ultra-lightweight die-cast chassis allows for accurate and seamless installation and rapid maintenance from the front.

Either free standing or for seamless integration into interiors, the slim design is sleek and chic as befits the latest innovation in digital content delivery. Benefit from excellent viewing angles, consistent vibrant colours, superb brightness and long lasting performance for high impact display projects.

Benefits

Care-free installation – with bundled solutions that deliver all you need to get your LED video wall up and running.

Large scale for perfectly detailed imagery – completely bezel-less design with high contrast rates deliver an unhindered viewing experience.

Slim design – with a flush rear profile, LED modules can be integrated very close to the wall with no gap necessary due to minimal heat emission.

Front serviceable modules – with front and rear access to the LED modules, maintenance is easy.

Visual excellence – high contrast and high brightness is inherent in LED delivery, benefit from NEC's long lasting quality.

NEC

NEC Australia nec.com.au		LED-N-018 2
Product information		
Product Name	LED-N-018	
Product Group	Indoor LED 1.86 mm LED panel	
Display		
Pixel Configuration	3-in-1 SMD (Black)	
LED type	SMD (1515)	
Panel Size [mm]	640×480	
Aspect Ratio	3:2	
Pixel Pitch [mm]	1.86	
Brightness (max.) [cd/m²]	800	
Lifetime	100000 hrs (50% brightness)	
Contrast Ratio (typ.)	5000: I	
Viewing Angle [°]	I40 horizontal / I40 vertical	
Dimming Capability	256 levels	
Colour Processing	I4 bit	
Colours	4.4 trillion	
LED Driving Method	I/30 dynamic scan	
Frame Rate	50/60 Hz	

Frame Rate	50/60 Hz
Refresh Rate [Hz]	< 3840
Colour Temperature [K]	2500 - 1000

Screen Resolution

Resolution	344 x 258
Resolution per m ²	289,050
Number of Pixel per module [dot]	172 × 86
Number of Pixel per card [dot]	14,792

Connectivity

Input Video Digital	I x HDMI 2.0; I x DP I.2; I x DVI-D
Input Control	Gigabit Ethernet

Electrical

Total Power Consumption [W]	55 typ. / 178 max.
Power Consumption typ. [W]	180 per m² (normal use)
Power Consumption max. [W]	580 per m²

Environmental Conditions

Operating Temperature [°C]	-10 to 50
Operating Humidity [%]	10 to 90



LED-N-018 NEC Australia | nec.com.au

Mechanical

Dimensions (W x H x D) [mm]	640 × 480 × 74
Dimensions (W \times H \times D) [mm] per module	$320 \times 160 \times 17$ or $160 \times 160 \times 17$

Weight [kg] 6.8

Additional Features

Shipping Content	LED Controller; LED Modules; Pixel Card Removal Tool; Spare Parts Kit	
Manufacturer	NEC	
Serviceability	Front Service	
IP Level	IP45	
Certifications	CCC; CE; ETL; FCC Class A; RoHS;RCM	
Warranty	3 years conditional warranty	

For more information:



nec.com.au



contactus@nec.com.au



131 632

Corporate Headquarters (Japan) NEC Corporation www.nec.com

Australia NEC Australia Pty Ltd www.nec.com.au

North America (USA) NEC Corporation of America www.necam.com

Asia Pacific (AP) NEC Asia Pacific www.sg.nec.com

Europe (EMEA) NEC Enterprise Solutions www.nec-enterprise.com

v.01.07.22 | LED-N-018

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

