

Product Information Sheet Indoor LED 3.8 mm 220" HD Bundle

LED-FA038i2-220





Nothing less than magnificent

For premium large surface visualization, NEC's fine pitch LED FA Series Bundles provide standard resolution, direct view LED screens for applications in meeting spaces and exclusive signage. With a depth of just 5cm, plus complete internal cabling, the FA series presents a sleek profile for a bezel-free viewing experience. With excellent viewing angles, consistent vibrant colours and superb brightness; the FA Series delivers content that gets noticed. Native HD, FHD and UHD resolutions are achieved through configuration of multiple 16:9 cabinets which are bundled with a power bar, framing, mounting and controller. With pixel pitches starting from 1.2mm at 110" screen size in FHD resolution, optimum viewing distances from 2m are achieved. Designed with high quality components and maintenance access from the front, the FA Series provides a display solution with longevity and good return on investment. The prime solution for boardrooms, auditoria, luxury retail environments and control rooms.

Benefits

Care-free installation – with bundled solutions that deliver all you need to get your LED video wall up and running.

Large scale for perfectly detailed imagery – completely bezel-less design with high contrast rates deliver an unhindered viewing experience.

Secure performance for demanding applications – with high-end components and redundant module design with additional power supply and data cards to ensure ongoing operations with a minimal loss of brightness levels.

Superb readability in bright light environments – high brightness levels of up to 1200 cd/m², along with wide viewing angles deliver clear messages to your audience even under varying and demanding ambient conditions.

Slim design – with a flush rear profile, LED modules can be integrated very close to the wall with no gap necessary due to minimal heat emission.

NEC

		 1
Product information		
Product Name	LED-FA038i2-220	
Product Group	Indoor LED 3.8 mm 220" HD Bundle	
Order Code	LED-FA038i2-220	
Display		
Pixel Configuration	3-in-1 SMD (Black)	
LED type	SMD (1515)	
Screen Size [inch/cm]	220 / 559	
Aspect Ratio	16:9	
Pixel Pitch [mm]	3.8	
Brightness (max.) [cd/m²]	1200	
Lifetime	100000 hrs (50% brightness)	
Contrast Ratio (typ.)	7000:1	
Viewing Angle [°]	160 horizontal / 160 vertical	
Dimming Capability	256 levels	
Colour Processing	16 bit	
Colours	281 trillion	
LED Driving Method	1/15 dynamic scan	
Frame Rate	50/60 Hz	
Refresh Rate [Hz]	< 2880	
Colour Temperature [K]	3000 - 9500	
Screen Resolution		
Resolution	1280 x 720	
Resolution per m ²	69252	
Number of Pixel per module [dot]	160 x 90	
Number of Pixel per card [dot]	40 x 45	
Connectivity		
Input Video Digital	1 x 3G SDI; 1 x DVI-D; 1 x HDMI	
Input Control	1 x GenLock; 1 x LAN	
Electrical		
Total Power Consumption [W]	3008 typ. / 7680 max.	
Power Consumption typ. [W]	235 per m² (normal use)	
Power Consumption max. [W]	600 per m²	
Environmental Condition	s	
Operating Temperature [°C]	-20 to 40	



Operating Humidity [%]

10 to 80

LED-FA038i2-220 NEC Australia | nec.com.au

Mechanical

Dimensions (W x H x D) [mm]	4,864 x 2,856 x 81	
Dimensions (W x H x D) [mm] per module	608 x 342 x 50	
Weight [kg]	660	
Additional Features		
Shipping Content	2x LED Controller; LED Modules [64 Cabinets, 512 Pixel Cards); Overframe Kit (8x8); Pixel Card Removal Tool; Power Bar; Spare Parts Kit; Wall mount (8x8)	
Manufacturer	NEC	
Serviceability	Front Service	
IP Level	IP20	
Certifications	CCC; CE; ETL; FCC Class A; RoHS;RCM	
Warranty	5 years conditional warranty	

For more information:



nec.com.au



contactus@nec.com.au



131 632

Corporate Headquarters (Japan)NEC Corporation

www.nec.com

Australia NEC Australia Pty Ltd www.nec.com.au

North America (USA) NEC Corporation of America www.necam.com

Asia Pacific (AP) NEC Asia Pacific www.sg.nec.com

Europe (EMEA)NEC Enterprise Solutions
www.nec-enterprise.com

v.20.01.24 | LED-FA038i2-220

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

