

### Product Information Sheet

# LED-A019i - Indoor LED 1.944 mm Poster





## Mobile messaging with meaning

Move your message to where it's needed most, delivering more meaning right where it needs to be seen. NEC's LED A Series provides a free-standing message board which demands attention with vivid, high contrast content that shines out with high bright LED brilliance.

Robust enough for use in public spaces, the A Series is the ideal replacement for static roll-up banners. The dynamic content can be updated as needed to provide wayfinding assistance or promotional signage in hotel lobbies, convention centres, at trade fairs or in shopping malls.

Slim and light in weight with 1.9mm Pixel Pitch.

#### Benefits

Robust stand design – safe for use in areas of high public footfall.

Screen protection – with a clear protection layer the LEDs are guarded against damage whilst unhindered from delivering their full visual brilliance.

**Mobile usage** – light-weight and slim the LED poster provides a stand-alone design which can be moved to wherever it is needed.

Easy integration – the poster can also be integrated into walls thanks to its removable stand and slim depth.

**Connectivity availability** – with HDMI inputs, USB port and app based content delivery the A series is appropriately equipped.

NEC Australia | nec.com.au

Product information	
Product Name	LED-A019i
Product Group	Indoor LED 1.944 mm All-in-one Solution
Order Code	LED-A019i
Display	
Pixel Configuration	3-in-1 SMD (Black)
LED type	SMD (1515)
Pixel Pitch [mm]	1.944
Brightness (max.) [cd/m²]	1000
Lifetime	100000 hrs (50% brightness)
Contrast Ratio (typ.)	4500:1
Viewing Angle [°]	150 horizontal / 140 vertical
Dimming Capability	256 levels
Colour Processing	13 bit
Colours	281 trillion
LED Driving Method	1/27 dynamic scan
Frame Rate	50/60 Hz
Refresh Rate [Hz]	< 2880
Colour Temperature [K]	3000 - 9500
Screen Resolution	
Resolution per m <sup>2</sup>	257307
Number of Pixel per module [dot]	288 x 972
Number of Pixel per card [dot]	144 x 108
Connectivity	
Input Video Digital	1 x HDMI
Power In	1 x Power In
Input Control	1 x LAN
Pro service de la constante de	
Electrical	
Power Consumption typ. [W]	250 per m² (normal use)
Power Consumption max. [W]	750 per m²
Environmental Condition	s
Operating Temperature [°C]	-10 to 40
Operating Humidity [%]	10 to 80
Mechanical	
Dimensions (W x H x D) [mm] per module	572 x 1,902 x 35
Weight [kg]	32



#### **Additional Features**

Manufacturer	NEC
IP Level	Front: IP20; Rear: IP20
Certifications	CCC; CE; ETL; FCC Class A; RoHS ;RCM
Warranty	3 years conditional warranty

#### For more information:



nec.com.au



contactus@nec.com.au



131 632

**Corporate Headquarters (Japan)** NEC Corporation www.nec.com

**Australia** NEC Australia Pty Ltd www.nec.com.au

North America (USA) NEC Corporation of America www.necam.com

Asia Pacific (AP) NEC Asia Pacific www.sg.nec.com

**Europe (EMEA)** NEC Enterprise Solutions www.nec-enterprise.com

v.20.01.16 | LED-A019i

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

