Product Information Sheet Indoor LED 1.56 mm Black Face LED Panel

LED-PRO-N-015





Essential bundles of brilliance

For bezel-free viewing experiences using vivid LED technology, NEC's LED Solution delivers essential visualization for scalable large digital surfaces. Even for cost-conscious deployments for presentation and signage, NEC's LED Solution provides long lasting NEC quality with industrial-grade power supplies in easy to install.

The ultra-lightweight die-cast chassis allows for accurate and seamless installation and rapid maintenance from the front.

Either free standing or for seamless integration into interiors, the slim design is sleek and chic as befits the latest innovation in digital content delivery. Benefit from excellent viewing angles, consistent vibrant colours, superb brightness and long lasting performance for high impact display projects.

Benefits

Care-free installation – with bundled solutions that deliver all you need to get your LED video wall up and running.

Large scale for perfectly detailed imagery - completely bezel-less design with high contrast rates deliver an unhindered

viewing experience.

Slim design – with a flush rear profile, LED modules can be integrated very close to the wall with no gap necessary due to minimal heat emission.

Front serviceable modules – with front and rear access to the LED modules, maintenance is easy.

Visual excellence – high contrast and high brightness is inherent in LED delivery, benefit from NEC's long lasting quality.



Product information	
Product Name	LED-PRO-N-015
Product Group	Indoor LED 1.56 mm LED panel

Display

Pixel Configuration	3-in-1 SMD (Black)
LED type	SMD (1010)
Panel Size [mm]	600×337.5
Aspect Ratio	16:9
Pixel Pitch [mm]	1.56
Brightness (max.) [cd/m²]	900
Lifetime	100000 hrs (50% brightness)
Contrast Ratio (typ.)	5000:1
Viewing Angle [°]	140 horizontal / 140 vertical
Dimming Capability	256 levels
Colour Processing	14 bit
Colours	4.4 trillion
LED Driving Method	I/30 dynamic scan
Frame Rate	50/60 Hz
Refresh Rate [Hz]	< 3840
Colour Temperature [K]	2500 - 1000

Screen Resolution

Resolution	384 x 216
Resolution per m ²	409,600
Number of Pixel per module [dot]	192 × 108
Number of Pixel per card [dot]	82,944

Connectivity

Input Video Digital	I x HDMI 2.0; I x DP I.2; I x DVI-D
Input Control	Gigabit Ethernet

Electrical

Total Power Consumption [W]	75 typ. / 200 max.
Power Consumption typ. [W]	370 per m² (normal use)
Power Consumption max. [W]	989 per m²

Environmental Conditions

Operating Temperature [°C]	-10 to 50
Operating Humidity [%]	10 to 90

Mechanical

Dimensions ($W \times H \times D$) [mm]	600 x 337.5 x 58
Dimensions (W x H x D) [mm] per module	300 x 168.75 x 8
Weight [kg]	4.7
Additional Features	
Shipping Content	LED Controller; LED Modules; Pixel Card Removal Tool; Spare Parts Kit
Manufacturer	NEC
Serviceability	Front Service
IP Level	IP40
Certifications	CCC; CE; ETL; FCC Class A; RoHS;RCM
Warranty	3 years conditional warranty

For more information:

www nec.com.au

contactus@nec.com.au

131 632

Corporate Headquarters (Japan) NEC Corporation www.nec.com

v.23.09.21 | LED-PRO-N-015

Australia NEC Australia Pty Ltd

www.nec.com.au

North America (USA) NEC Corporation of America www.necam.com

Asia Pacific (AP) NEC Asia Pacific www.sg.nec.com Europe (EMEA) NEC Enterprise Solutions www.nec-enterprise.com

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

©2021 NEC Australia Pty Ltd. All rights reserved. NEC and NEC logo are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.

